



## THERM-A-STRIP

### Flexible intumescent strip

#### INTRODUCTION

THERM-A-STRIP is a low pressure intumescent strip material which has been developed for applications where a pressure forming product is disadvantageous. The degree of expansion is moderate in order to provide some resistance to erosion.

#### THE PRODUCT

THERM-A-STRIP has been developed to provide excellent sealing properties combined with the benefit of a flexible strip of intumescent material. It is particularly useful in cases where there is a possibility of localized flaming due to combustible products since it generates fire retardant gases when heated.

#### APPLICATION

THERM-A-STRIP intumescent strip can be supplied in a variety of shapes so that it can be used in a wide range of applications including gaskets for ironmongery protection, locks, latches, bolts, hinges etc. It is also useful in applications where the gap to be filled is small and the fire retardant properties are beneficial such as overpanels and glazing applications.

#### DESCRIPTION


THERM-A-STRIP is a flexible phosphate based intumescent product giving an approximate ten fold increase in volume when exposed to heat. Its activation temperature is around 180°C.

THERM-A-STRIP is supplied in a natural white finish which, because of its resistance to both atmospheric moisture and carbon dioxide, requires no additional surface protection.

The material may be decorated with a wide range of conventional finishes without impairing the performance. It is available with or without a self-adhesive backing strip.

#### AVAILABILITY

THERM-A-STRIP is supplied as standard white but it can be coloured if required.\*




Contact our Technical Department for further information.

Nominal sizes are available in the following dimensions:

10 mm x 2 mm  
15 mm x 2 mm  
20 mm x 2 mm  
25 mm x 2 mm  
30 mm x 2 mm  
38 mm x 2 mm


Other sizes are available and in standard lengths of 1050 mm or 2100 mm

Other thicknesses from 1 mm upwards, widths up to 130mm wide and lengths up to 3000 mm are available on request.



#### THERM-A-STRIP

THERM-A-STRIP  
15mm x 2mm (Doors)  
10mm x 2mm (Screens)



#### TEST EVIDENCE

THERM-A-STRIP meets the requirements for fire and smoke performance of BS476 :

parts 20, 22 & 31.1 . It has also passed the more exacting standards required by Certifire. It is currently being evaluated to the requirements of BS EN 1634-1.

Copies of test reports and other evidence are available on request.

#### RELATED PRODUCTS

When this product is used for 60 minute glazing applications it may be beneficial to use it in conjunction with other products to enhance its performance.

Please contact our Technical Department for further advice.



\* Colours may vary slightly between examples illustrated in print, online and actual samples - which will depend upon lighting conditions in situ.